

WIDTH: 250 / 270 cm

WEIGHT: 590 g/sqm



PAVILION STRUCTURE



STORAGE BUILDING (LOGISTICS)



EVENT STRUCTURE

G U A R A N T E E S A N D L A B E L S




ADVANTAGES

- FERRARI® PRÉCONTRAIT TECHNOLOGY
- EXCEPTIONALLY LONGEVITY
- UV RESISTANT
- FLAME RETARDANT
- EXTREME WHITE
- SIMPLIFIED MAINTENANCE: FORMULA S
- EXCEPTIONAL LUMINOSITY
- CR TREATMENT

COLOURS AND REFERENCES

(COLOURS GIVEN FOR INDICATION)



Ref. 502-8104S CR White

TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	PRÉCONTRAIT® 502-8104S TRANSLUCENT	TERSUISSE
TREATED YARN	1100 dtex "CR" PES HT	
WEIGHT	590 g/sqm	EN ISO 2286-2
WIDTH	250/270 cm	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	28/28 daN	DIN 53.363
ADHESION	10 daN/5 cm	EN ISO 2411
FINISH	FORMULA S FLUORIDATED VARNISH WELDABLE	
LIGHT TRANSMISSION	19%	
FLAME RETARDANCY	M2/NFP 92.503 - B1/DIN 4102 - M2/UNE 23727-90 - CALIFORNIA STATE FIRE MARSHAL - NFPA 701 - BS 7837 - SP FULL SCALE TEST - METHOD 2205 - SIS 650082	
EXTREME WORKING TEMPERATURES	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM	ISO 9000	

The technical characteristics shown are average values given as a guide and may be modified.

FERRARI

