

WIDTH: 250/270 cm

WEIGHT: 670 g/m<sup>2</sup>



EVENT STRUCTURES

G U A R A N T E E S A N D L A B E L S



### AVANTAGES

- FERRARI PRÉCONTRAIT® TECHNOLOGY
- EXCEPTIONALLY LONGEVITY
- UV-RESISTANT
- FLAME RETARDANT
- EXCELLENT OPACITY
- SIMPLIFIED MAINTENANCE: FORMULA S
- 502-8103S: EXCEPTIONALLY LIGHT

### COLORIS & RÉFÉRENCES

(COLORIS INDICATIFS)



Ref. 502- 8103S Opaque  
 White/White

### TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	PRÉCONTRAIT® 502-8103S OPAQUE	
YARN	1100 dtex PES HT	TERSUISSE
WEIGHT	670 g/sqm	EN ISO 2286-2
WIDTH	250/270 cm	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	28/28 daN	DIN 53.363
ADHESION	10 daN/5 cm	EN ISO 2411
FINISH	FORMULA S FLUORIDATED VARNISH WELDABLE	
FLAME RETARDANCY	M2/NFP 92.503 - B1/DIN 4102 - M2/UNE 23727-90 - CALIFORNIA STATE FIRE MARSHAL NFPA 701 - BS 7837 - SP FULL SCALE TEST - METHOD 2205 - SIS 650082	
EXTREME WORKING TEMPERATURES	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM	ISO 9000	

The technical characteristics shown are average values given as a guide and may be modified.

**FERRARI**

